



Tim-bor Insecticide is an EPA-registered termiticide and insecticide for use by professional Pest Control Operators. **Tim-bor** is a unique product for the protection and remedial treatment of wood against all wood-destroying organisms.

TIM-BOR APPLICATION:

Oversized containers help prevent careless spills and minimizes splashing during mixing.

Adding **Tim-bor** to water:

- Having water in the mixing container before adding **Tim-bor** reduces dust and speeds the mixing process.
- Adding water to dry powder is not recommended. This tends to form clumps of material that dissolve slowly.
 1. Estimate the amount of **Tim-bor** solution needed to complete the job. Approximately 5 gallons of solution are needed to cover 1,000 square feet of wood surface area. This amount can vary depending on the moisture content and species of wood.
 2. Using a slightly oversized container (bucket), fill to about 80% of the final required volume, then add 1 lb. of **Tim-bor** powder per gallon of required solution while stirring. The remainder of the water is then added and the solution is agitated until all of the product has dissolved.

EXAMPLE

Prepare 5 gallons of 10% **Tim-bor** solution:

- a. Add four (4) gallons of clear water to a six-gallon bucket.
- b. Add five (5) one lb. measures of **Tim-bor** while gently stirring.
- c. Add enough water to bring the final volume to 5 gallons, and continue to stir until all of the **Tim-bor** has dissolved.
- d. Agitate the solution briefly at the beginning of each spray job, or after the solution has been standing for an extended period. Warm water will dissolve **Tim-bor** more rapidly.

Do not spray or spill onto soil or foliage. **Tim-bor** may leave white crystals on concrete or masonry work after drying.

METHOD

1. Spray wood evenly, using a medium to coarse spray at low pressure.
2. Ensure that all accessible wood surfaces are thoroughly wetted. Wood will absorb the **Tim-bor** solution at different rates. Surfaces that absorb solution rapidly should be sprayed again.

For serious infestations, apply two sprays 1-24 hours apart.

Two sprays applied 1 - 24 hours apart for remedial use. When accessible, drill and inject solution directly into wood where galleries or kickholes are detected. See Label instructions on product packaging for details.

Available from www.PRGinc.com 800-774-7891